

kod	staničení dif.stan.	poloměr parametr	1.tečna	yh	xh	sm1
			2.tečna sečna	ys yt	xs xt	sm2 alfa
ZÚ	0.000	0.000	0.000	651748.508	1152468.906	309.4213
	46.696	0.000	0.000	0.000	0.000	309.4213
			46.696	0.000	0.000	0.0000
TK	46.696	-50.000	11.513	651702.322	1152475.791	309.4213
	22.632	0.000	11.513	651694.949	1152426.338	280.6047
			22.440	651690.934	1152477.489	-28.8166
KT	69.329	0.000	0.000	651679.951	1152474.035	280.6047
	47.023	0.000	0.000	0.000	0.000	280.6047
			47.023	0.000	0.000	0.0000
TK	116.352	300.000	16.227	651635.093	1152459.929	280.6047
	32.422	0.000	16.227	651545.103	1152746.114	287.4850
			32.407	651619.614	1152455.062	6.8803
KT	148.774	0.000	0.000	651603.699	1152451.892	287.4850
	44.752	0.000	0.000	0.000	0.000	287.4850
			44.752	0.000	0.000	0.0000
KÚ	193.526	0.000		651559.809	1152443.151	287.4850

staničení	výška	poloměr	tečna	vzepětí	spád %	délka	mezipřímá
0.000	418.640	0.000	0.000	0.000	0.000	9.000	0.000
9.000	418.640	-300.000	9.000	-0.135	-6.000	38.981	22.481
47.981	416.301	500.000	7.500	0.056	-3.000	80.506	51.006
128.487	413.886	800.000	22.000	0.302	2.500	65.039	43.039
193.526	415.512	0.000	0.000	0.000			